

SS 80 M R290


230 V / 50 Hz













SELF-CONTAINED ICE CUBE MACHINE



FEATURES

- ▶ PRODUCES SOLID GOURMET CRYSTAL CLEAR ICE CUBES
- ▶ ELECTRONIC CONTROL THAT ENHANCES THE PERFORMANCE OF THE MACHINE AND ALLOWS IT TO ADAPT TO EXTREME CLIMATES
- ▶ A3S: ANTI-SCALE SPRAY SYSTEM. THE ITV PATENTED SPRAY SYSTEM WITH FLEXIBLE NOZZLES AVOIDS LIMESCALE DEPOSITS WITH SMALL VIBRATIONS
- ▶ SMART FRONT VENTILATION SYSTEM (SFVS) ALLOWS BUILT-IN INSTALLATION OF THE UNIT
- ▶ "NEVER STOP" MOTOR PUMP DEVELOPED BY ITV. ITS DESIGN WITHOUT SEALS PREVENTS FROM DETERIORATION IN HARD WATER
- ▶ ON/OFF LIGHTED ROCKER SWITCH / NEW PCB MOUNTED AT THE BOTTOM
- ▶ AISI 304 STAINLESS STEEL BODY
- ▶ THE DISAPPEARING DOOR REDUCES THE FOOTPRINT OF THE MACHINE AND AVOIDS ACCIDENTS
- ▶ TROPICALIZED MACHINES (T CLASS) / HEIGHT ADJUSTABLE LEGS FROM 105MM A 155MM
- ▶ NATURAL GAS R290 WITH VERY LOW GLOBAL WARMING POTENTIAL WHICH ALSO REDUCES THE ENERGY CONSUMPTION
- ▶ AN ANTI-LIMESCALE FILTER IS ADVISED IN HARD WATER AREAS (WATER HARDNESS OVER 30 °fH)



	 24 H	 10°C (Kg)	 10°C (Kg)	 21°C (Kg)	 15°C (Kg)	 STOCK (Kg)	 (mm)	 (mm)	
SS 80 M A		85	79	40	Width 645 Depth 640 Height 865*	Width 720 Depth 710 Height 1.000		SS M 22 Gr 35 (Ø) x 35 mm (H) Average dimensions	
SS 80 M W		87	81						


* WITH LEGS 970/1.020

ACCESSORIES

INCLUDED




NOT INCLUDED (OPTIONAL)







LEFT SIDE VIEW




FRONTAL VIEW



REAR VIEW



TOP VIEW



* All measurements in mm.

OPERATING CONDITIONS

PRODUCTION 50Hz


±10% V

5°C/43°C

5°C/35°C

1 bar/6 bar

48 Ice cubes/cycle



V	Hz	ph
230	50	1N

SS 80 M AIR COOLED

°C °F	10° 50°	15° 60°	21° 70°	30° 86°
	10° 50°	85	82	77
21° 68°	82	79	75	70
32° 90°	77	73	66	60
43° 109°	67	62	54	50

SS 80 M WATER COOLED

°C °F	10° 50°	15° 60°	21° 70°	30° 86°
	10° 50°	87	84	80
21° 68°	83	81	77	72
32° 90°	78	75	72	66
43° 109°	72	70	66	59

MODELS

MODELS	+c° -c°	ASHRAE CONDITIONS (W) (BTu/h)	(W) 43°C	(n.) (mm²)	FUSE	100 Kg (Kwh)	(l/h)	HEAT REJECTED (W) (BTu/h)	(Kg)	(Kg)	(m³)
SS 80 M A		1.967 6.715	752	3 1,5	10	17	10.1	1.344 4.588	62	66	0,51
SS 80 M W		1.967 6.715	828	3 1,5	10	15,8	45,1	1.344 4.588	62	66	0,51



Subject to certain limitations and exclusions. Only spare parts.



9001
14001

