




NATURAL
REFRIGERANT
R290

Key Features

The IM-45NE-HC and IM-45CNE-HC are compact sized cube ice makers, which utilises Natural Refrigerant R290.

- ✓ Energy efficient, with savings of 20% compared to HFC equivalent model.*
- ✓ Smallest member of the Emerald Class, Hoshizaki's new range of climate friendly ice makers.
- ✓ Can produce up to 46kg of cube ice per 24 hours (AT.10°C.WT.10°C).
- ✓ Unique ice making system that has an automatic rinse cycle. After every new batch of ice, the water reservoir drains and refills with fresh water. System comes with a magnetic water pump that has no direct coupling, which prevents any leakage.
- ✓ Closed water circuit offers the ultimate contamination protection, by reducing the number of points at which impurities can enter the ice making process.
- ✓ Electronically controlled to ensure an optimised ice making process under varying circumstances without the need for physical adjustments. Quality of ice is always consistent.
- ✓ Easily cleanable air filter allows end-users to carry out routine cleaning schedules. Extends product life expectancy and reduces the frequency and costs of maintenance call-outs.
- ✓ Stainless steel exterior with integrated door handles provides a hygienic and high quality finish.

Based on Internal comparative study. Please contact your local sales branch to find out more.



Ice: Standard Cube (L)
Size: Approx. 28 x 28 x 32mm

Available Models

Model	Air Cooled	Water Cooled
IM-45NE-HC	✓	
IM-45CNE-HC	✓	

Bins

Model	Type of Bin	Max. Bin Capacity approx.
IM-45NE-HC	Self-contained	18kg
IM-45CNE-HC	Self-contained	15kg

Production

Model	Ice Production per 24h approx.	Temperature	Water Consumption per 24h approx.
IM-45NE-HC	Approx. 40kg (5mm) / 46kg (15mm)	AT.10°C, WT.10°C	0,18m ³
	Approx. 36kg (5mm) / 42kg (15mm)	AT.21°C, WT.15°C	0,11m ³
	Approx. 30kg (5mm) / 34kg (15mm)	AT.32°C, WT.21°C	0,10m ³
IM-45CNE-HC	Approx. 40kg (5mm) / 46kg (15mm)	AT.10°C, WT.10°C	0,18m ³
	Approx. 36kg (5mm) / 42kg (15mm)	AT.21°C, WT.15°C	0,11m ³
	Approx. 30kg (5mm) / 34kg (15mm)	AT.32°C, WT.21°C	0,10m ³

For more information visit our website at www.hoshizaki-europe.com

Hoshizaki Europe B.V. retains the right to change products and their specifications without prior notice.



